Acoustic Panels



Brand: **Zintra**

Collections: 3D Panel

Applications: Walls



Acoustic Panels



3D Panel Peaks Detail

2 of 7

Acoustic Panels

Zintra 3D Panel Peaks offer both an intriguing design element and functional acoustic enhancement. Add depth and design to flat surfaces which absorb sound and cancel out soundwaves.

| ✓ Acoustic✓ Easy Install | ✓ Bleach Cleanable | ✓ Easy Clean | |
|---|---|---|--|
| Description | Seamlessly joined, our 3D Wall Panels offer both an intriguing design element and functional acoustic enhancement for straight or curved walls. These narrow panels boast a small pattern repeat, facilitating easy adjustment for wall-to-wall fitting without the need for custom drawings. | | |
| | of angular protrusions arranged in | eaks of mountains. This panel features a series a symmetrical pattern, creating a dynamic and and intricate design make it suitable for a n offices and conference rooms to | |
| | serves a functional purpose by enh | cribute to the aesthetics of a space, but it also ancing sound absorption and cancelling out ds depth and dimension to flat surfaces, tivating focal points. | |
| | Also available in Batten 2, Batten 4 and Batten 6 | | |
| | pattern. Designed to bring a touch your space. Featuring alternating w | e timeless appeal of the board and batten of architectural elegance and visual interest to ide boards and vertical battens, this captivating ured surface. Its classic yet versatile design and character to any project. | |
| | Not suitable as a free standing prod | duct. | |
| Composition | Zintra Acoustic Panel - 100% Soluti | on Dyed (Colour Through) Polyester | |
| | 12mm (1/2") -Density 2.4 kg /m² 0.5 lb/ft² | | |
| Sustainability | Zintra is made from 100% recyclabl | e materials. | |
| | 60% post-consumer recycled content from PET bottles. | | |
| | 35% pre-consumer recycled content from PET chips | | |
| | • 5% polylactic acid (PLA) | | |
| | | | |



Acoustic Panels

| Dimensions | Peaks: | |
|---------------------------|--|--|
| | • 3 strips / set, 2.4m² (26.3SF) | |
| | • 305mm (12") w x 2745mm (108.1") h x 40mm (1.6") d / strip | |
| | **Please note: Visible width 289mm (11.3") | |
| Fire Rating | ASTM-E84 – Class A classification AS ISO 9705 – 2003 – Group 1 classification EN-13501 – B-s2-d0 classification | |
| Supplied As | • Peaks 3 Strips (Set) 2.4m² (26.3SF) | |
| Assembly & Delivery | Ships Flat Packed. Refer Installation instructions. | |
| | Recommended 2 People assembly | |
| | Go to the Technical Documents and download the Installation Guide for more details. | |
| Suggested Installation | Go to Technical Documents and download the Installation Guide for more details. | |
| Care Instructions | Vacuum to remove dust. | |
| | Dab Zintra with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth. | |
| | For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry. | |
| | Always test in an inconspicuous area first and if you don't see the expected results, contact us. | |
| Warranty | Visit FAQ for more details. | |
| Customisable | Zintra Acoustic Panel - 100% Solution Dyed (Colour Through) Polyester | |
| | 12mm (1/2") - Density 2.4 kg /m² 0.5 lb/ft² | |
| Additional Comments | NRC 0.45 | |



Acoustic Panels

How to Specify 1. Select Design

2. Select Zintra Colour



5 of 7

Color & Finish Options

Zintra 12mm Solid PET







Acoustic Panels





Storm







Zintra Timber









Eucalyptus

Ironbark

Merbau

Spotted Gum

zintraacoustic.com